


CONTINUOUS BELAY SYSTEM | OTHER MATERIALS





WIRE ROPES & ACCESSORIES

> GENERAL INFORMATION

> WIRE ROPES


> WIRE ROPE ACCESSORIES

> TOOLS


> HARDWARE

GENERAL INFORMATION






INSTALLING A WIRE ROPE



ANGLES & FORCES



TRANSPORT & UNWINDING OF WIRE ROPES



SOME EXAMPLES OF DEFAULT



Increase in diameter due to the extrusion of the core



Kink



External wear



Broken wires



Reduction in wire rope diameter (hollowstand)



Broken wires in the grooves

WIRE ROPES

USE							
LIFELINE		. •۲	C., ר		ר. <mark>,</mark> ה		
ZIPLINE		C.,.	ີ		ີີ		
OBSTACLE SUPPORTING WIRE ROPE	ר <u>،</u> ٦						
BRACE CABLE	ר <u>،</u> ٦						
HANDRAIL	. ••			C., ר			
SAFETY LOOP	. ••		C.,.	C., ר	C.,.		
TECHNICAL INFORMATION							
CORE	Wire strand core	Fiber core	Wire strand core	Wire strand core	Wire strand core		
STRAND RESISTANCE	1770 N / mm2	1770 N / mm2	2160 N / mm2	1770 N / mm2	1960 N / mm2		
MIN. BREAKING LOAD	110 kN	110 kN	142 kN	60 kN	94 kN		
MAX. WORKING LOAD	22 kN	22 kN		12 kN	19 kN		
SAFETY FACTOR	5	5	5	5	5		



7 x 19 WSC GALVA-**NIZED WIRE ROPE** Ø12 mm (Ø 0.47in)

REF : CA04

REF : CA04-B100 100 m (3937 in) (328 ft) REEL

REF : CA04-B250 250 m (9842 in) (820 ft) REEL



6 x 7 FC LANG'S LAY **GALVANIZED WIRE** ROPE Ø12 mm (Ø 0.47in)

REF : CA05

REF : CA05-B250 250 m (9842 in) (820 ft) REEL

REF : CA05-B500 500 m (19685 in) (1640 ft) RFFI




6 x 26 WSC GALVA-**NIZED SWAGED WIRE** ROPE IWRC Ø12 mm (Ø 0.47in)

REF:CA12

REF : CA12-B250 250 m (9842 in) (820 ft) REEL

REF : CA12-B500 500 m (19685 in) (1640 ft) REEL



7 x 19 WSC Ø12 mm **RED PLASTIC COATED** WIRE ROPE Ø10 mm INT (Ø 0.39 in) / 12 mm (Ø 0.47in) EXT

REF : CA01 RED | CUT TO SIZE

REF : CA01-B200 RED | 200 m (7874in) (656 ft) REEL

REF : CA02 GREEN | CUT TO SIZE



19x7 WSC ROTATION RESISTANT GALVA-NIZED WIRE ROPE Ø12mm (Ø 0.47in)

REF : CA11-B250 250 m (9842 in) REEL

WIRE ROPE ACCESSORIES



Ø12 mm (0.47 in) SWAGED THIMBLED WIRE ROPE 2 SOLID THIMBLES



- Can resist tensions above 6000 daN : the wire rope thimbles doesn't deform under high tension
- Ø12 mm 7x19 WSC
- 2 swaged solid thimbled ends
- Length : cut to size | Up to10 m (33 ft) Weight : 5 kg (11 lbs) for 7 m (23 ft)

Ø12 mm (0.47 in) SWAGED THIMBLED WIRE ROPE 1 SOLID THIMBLE

REF : CA08-10 CUT TO SIZE

- Can resist tensions above 6000 daN
- Ø12 mm 7x19 WSC (Galvanized wire rope sling)
- 1 swaged solid thimbled end
- 1 free end
- Length : cut to size | Until 10 m (33 ft)
- Weight : 6 Kg (13 lbs) for 10 m (33 ft)

Ø12 mm (0.47 in) SWAGED THIMBLED WIRE ROPE 2 THIMBLES

REF : CA06-10 CUT TO SIZE

- For tensions below 6000 daN
- Ø12 mm 7x19 WSC (Galvanized wire rope sling)
- 2 swaged thimbled ends
- Length : cut to size | Up to 10 m (33 ft)
- Weight : 4.6 kg (10 lbs) for 7 m (23 ft)

WIRE ROPE CLIP « CE » FOR Ø12 mm (0.47 in) WIRE ROPE

REF: QU130-12

- Hot drop forged wire rope clip
- Compliant with European Standard EN 13411-5
- « Steel ends / Security / U-shaped wire rope clip »
- Weight : 130 g (0.3 lbs)



WIRE ROPE CLIP « DIN 741 » FOR Ø12 mm (0.47 in) WIRE ROPE

REF: QU52-13

- Zinc plated wire rope clip DIN 741 - Weight : 122 g (0.3 lbs)













SOLID ROPE THIMBLE S412-1/2

REF: QU13

- Allows 16 insert a connector and expert a strong tension on the
- wire rope
- For Ø12 mm (0,47 in) wire rope Weight : 270 g (0.6 lbs)

Ø13 mm WIRE ROPE THIMBLE

REF : QU01-13

- For Ø 12 mm (0,47 in) and Ø13 mm (0,51 in) wire rope - Weight : 80 g (0.2 lbs)



ALUMINIUM FERRULE N°13 FOR SWAGING 2 Ø12 mm WIRE ROPES

REF: QU36-13

- To attach 2 wire ropes together Aluminium ferrule Ø int : ½" in To crimp with crimping tool REF : OU01-42CFM
- Weight: 60 g (0.1 lbs)



2 CLEVIS TURNBUCKLE HR

REF: QU55-305 STROKE 305 mm (12 in) REF : QU55-457 STROKE 457 mm (18 in)

- Installed at the end of the zipline, to adjust zipline rope tension
- Threaded rod \emptyset : 22.2 mm (\emptyset 7/8 in)
- WLL : 3.27 t
- Weight : 4.3 kg (9.5 lbs) and 4.9 kg (10.8 lbs)



ELECTRO-HYDRAULIC CRIMPING TOOL - 120 kN (KLAUKE)





REF : OU01-42CFMTO PURCHASEREF : OU03FOR RENT

- Crimping tool for swaging lifeline ferrules, aluminium and copper ferrules
- 2 speed hydraulic pump with fast-forward, automatic return after crimping, manual return if needed
- Power : 120 kN
- Included : 1 battery (Lithium ion 18 V) MAKITA
- To be used with apairof dies adapted to the wire rope / not included
- Weight : 13 kg (28.7 lbs)



BATTERY FOR KLAUKE CRIMPING TOOL (MAKITA)

REF : OU10-5A

- Fast battery charger
- -18V/5A
- Weight : 640 g (1.4 lbs)



BATTERY CHARGER DC18RA - 18V (MAKITA)

REF: OU11

- 18 V - Weight : 950 g (2.1 lbs)



HAND-OPERATED HYDRAULIC CRIMPING TOOL 120 kN

REF : OU05-HK12042

- Crimping tool for manually swaging lifeline ferrules, aluminium fer and copper ferrules
- Power : 120 kN
- To be used with a pain of dies adapted to the wire rope / not included - Weight : 9.3 kg (20.5 lbs)





PAIR OF DIES « 13 / 95 » - MONOCABLE FERRULE Ø12 mm (Ø 0.47 in)

REF : OU02-1395 FOR CONTINUOUS BELAY SYSTEM FERRULES - Weight : 220 g (0.5 lbs) | Price per pair

PAIR OF DIES « 13 / 120 » - MONOCABLE FERRULE Ø1/2" in

REF: OU02-13120US FOR CONTINUOUS BELAY SYSTEM FERRULES



PAIR OF DIES « 13 / 235 » - FOR ALUMINIUM FER-RULES ON DOUBLE WIRE ROPE Ø12 mm (Ø 0.47 in)

REF : OU02-13235 - Weight : 220 g (0.5 lbs) | Price per pair



IZUMI S-20 MANUAL HYDRAULIC CUTTER

REF : OU08 - Weight : 2.8 kg (6.2 lbs)

IZUMI S-20 BLADE FOR MANUAL CUTTER

REF : OU09 - Weight : 37 g (0.1 lbs)

FLAT WEB SLING EYE

REF : OU15-150 FLAT WEB SLING EYE & EYE SWL 20kN - Length 1.5m (4'11") | Weight : 570 g (1.3 lbs)

REF : OU15-300 FLAT WEB SLING EYE & EYE SWL 20kN - Length 3m (9'10") | Weight : 1 kg (2.2 lbs)



CABLE PULLER

REF: OU06-LMG1 LMG1

- For wire rope Ø5-15 mm (Ø 0.2-0.6 in) - Load 20 kN | Weight : 1.62 kg (3.6 lbs)

REF: OU06-LMG2 LMG2

- For wire rope Ø8-20 mm (Ø 0.3-0.8 in) - Load 30 kN | Weight : 2.9 kg (6.4 lbs)



LEVER HOIST

 REF: OU14-250
 250 kg (551 lbs) ELEPHANT / Weight: 2.15 kg (4.8 lbs)

 REF: OU14-750
 750 kg (1764 lbs) ELEPHANT / Weight: 3.50 kg (7.7 lbs)

 REF: OU14-1600
 1600 kg (3527 lbs) ELEPHANT / Weight: 9.50 kg (21 lbs)

- ELEPHANT lever hoist specially designed for the tensioning of ziplines and heavy load handling



PIEZO EXPRESS BLOW TORCH 8900

REF : OU17

- Open and adjust the gas flow
- Piezo ignition and locking plate
- Weight : 630 g (1.4 lbs)
- Sold without gas cartridge
- Great autonomy (1h15)



GAS CARTRIDGE EXPRESS 8191

REF : CS05-8191 FOR EXPRESS 8900

For blowtorches or other appliances that use type 200 butane gas cartridges
 Weight : 190 g (0.4 lbs)



RATCHET PODGER SPANNER - 17 mm (0.67 in) and 19 mm (0.75 in)

REF: OU26-17 19

- Double wrench, ratchet

- Reversible right / left

- Weight : 475 g (1.1 lbs)



DRIFT PUNCH - 4 mm (0.15 in) (FACOM)

REF: OU12

- Diameter : 4 mm (0.15 in) - Weight : 60 g (0.1 lbs)



THREADLOCKER LOCTITE 243 - MEDIUM STRENGTH

REF: CS17-243 05

- Prevents loosening on vibrating connections
- Works on all metals, including passive substrates (e.g. stainless steel, alu-
- minium, plated surfaces) P1 NSF Reg. No.: 123000
- Color : Blue
- Weight : 5 g (0.01 lbs)

THREADLOCKER LOCTITE 270 - HIGH STRENGTH

REF: CS17-270 05

- High-strength general threadlocker for maximum efficiency
- Prevents loosening on vibrating connections
 Works on all metals, including passive substrates (e.g. stainless steel, alu-
- minium, plated surfaces) P1 NSF Reg. No.: 123006
- Color : Green
- Weight : 5 g (0.01 lbs)



HARDWARE



THREADED ROD

REF : QU57-12X1000 REF : QU57-18X1000 REF : QU58-18X1000 REF : AC10-1500

Ø M12 x 1 m (Ø 3.3 ft) / Classe : 4.8
 Ø M18 x 1 m (Ø 3.3 ft) / Classe : 4.8
 Ø M18 x 1 m (Ø 3.3 ft) / Classe : 8.8
 Ø M18 x 0.7 in) x 1.50 m (4.9 ft) WITH ACCESSORIES

- Fully threaded

WELDED CHAIN Ø6 x 42 mm (Ø 0.2 x 1.7 in)

0-0-0-0-0-

REF:QU09

- Weight : 620 g (1.4 lbs)

- Galvanized steel







BOW SHACKLE BOLT

 REF : QU112-325
 WORKING WLL : 32.5 kN

 REF : QU112-475
 WORKING WLL : 47.5 kN

 REF : QU112-650
 WORKING WLL : 65 kN

- Crosby[®] Bow shackle bolt and pin type G2130OC with thin bolt head and pin nut

- Complies with the Federal Specification RR-C-271D Type IVA, Grade A, Class 3 - High strengh alloy steel

riigh strengt alloy steel

2 EYE TURNBUCKLE

REF : QU53-08 Ø8 mm (Ø 0.3 in) REF : QU53-12 Ø12 mm (Ø 0.5 in)

GALVANIZED STEEL CLAMP Ø125 mm (Ø 4.92 in)

REF: PR16-GAL FOR PVC TUBE Ø125 mm (4.92 in)

- Internal diameter : Ø160mm (Ø 6.29 in)
- Eternal diameter : Ø220mm (Ø 8.66 in)
- Weight : 45 g (0.1 lbs)



REINFORCED CLEAR HOSE ØINT 22 mm (0.9 in) ØEXT 16 mm (0.6 in)

 REF : PR20-45
 LENGTH : 45 cm (17.71 in)

 REF : PR20-65
 LENGTH : 65 cm (25.59 in)



SALES, DELIVERY TERMS & CONDITIONS

GENERAL PRINCIPLES

These General Terms of Sale apply in their entirety to all sales of ALTUS / KOALA EQUIPMENT products in France and Worldwide.

They prevail over any general terms of purchase or other documents issued by the Client, regardless of the terms. Any order sent to ALTUS / KOALA EQUIPMENT implies unconditional acceptance of ALTUS / KOALA EQUIPMENT's prices and these General Terms of Sale. They supersede all previous general terms of sale.

The fact that ALTUS / KOALA EQUIPMENT does not invoke at a given time, any of these General Terms of Sale shall not be construed as a waiver to subsequently enforce any of the said terms.

Ordering

There are different ways of ordering :

- online on our website : www.koala-equipment.com

- by phone on 0033 (0)4 50 97 50 19 from Monday to Friday from 8am to 12am and from 1:30pm to 5pm (French hours) - by e-mail at : info@koala-equipment.com

- by fax on 0033(0)4 50 97 50 11 - or by (snail) mail : ALTUS / KOALA EQUIPMENT - 1191 route de Bidaille - 74930 SCIENTRIER - FRANCE.

To validate your order, please fill out the required information (selected products, payment method, delivery information, e-mail) and make your payment.

Orders can only be carried out by an adult (\geq 18 years old).

Confirmation of your order

Upon receipt of your order, a quote will be sent indicating the shipping cost of your package and the amount for the materials ordered. We undertake to send you this quote within 48 hours (French working days).

Upon receipt of our e-mail quote, 3 methods of payment are available to confirm your order :

- by credit card through a secured link.

- by phone with your credit card number.

- by check if your bank is in France.

The order will become final once ALTUS / KOALA EOUIPMENT has confirmed by e-mail.

Pricing

Product prices are shown without VAT. Your invoice will include VAT if applicable. The VAT rate applied will be the one in place in France when you validate your order. An order is validated when the payment is received. In case of a change in the VAT rate the new rate will apply to all those orders not validated with a payment. Product prices are exclusive of shipping costs, customs fees and tax.

All prices may be subject to typographical errors.

Discounts apply to the online store pre-tax prices and do not include transport fees. There are no discounts on the purchase of Freestanding courses.

Pricing could change due to exchange rate modifications.

Package, postage & shipping costs

Shipping costs will be charged in addition to the price of the product, according to the weight and size of the parcel. They are calculated as accurately as possible by choosing the most suitable carrier for your package based on your shipping address.

Upon receipt, open the package in front of the carrier. If damaged in shipping, inform the carrier by making all reservations on the carrier's delivery voucher as he alone is responsible. Confirm in writing by registered letter within three days. The shipping company should compensate you.

Payment

You can make your payment by check if your bank is in France or by credit card which is the fastest and the most convenient method.

Credit cards issued by banks outside France must be international bank cards. When paying by credit card, the amount of your order is debited at the time of dispatch.

Payment by check is only possible for checks in Euros drawn on a bank in France. The check will be cashed upon receipt.

The check should be made payable to «ALTUS / KOALA EQUIPMENT», and sent to the following address :

ALTUS / KOALA EOUIPMENT 1191 Route de Bidaille 74930 SCIENTRIER FRANCE

The items will only be sent once the check has been cashed.

Retention of title

The goods remain our property until full payment. Risks relating to the goods sold (loss, damage) are however transferred to the buyer upon dispatch from our premises.

Invoices

The invoice is sent in the package with your delivery. If the billing address is different from the delivery address, the invoice will be sent by e-mail or by post. Please note that purchase orders and confirmations cannot serve as invoices.

Complaints

Any dispute about the nature or quantity of items received must be communicated to us within 48 hours of receipt. We will attempt to solve any difficulties to do with your orders and their payment with you directly. Understanding and good will can dispel many incidents ... of which there are thankfully few.

However, if no solution were to be found, all disputes will be dealt with by the Commercial Court, 10 rue de l'Hotel de Ville, 74200 Thonon les Bains, France.

Cancellation rights

You have 7 days after purchase, to return a product without having to justify its return. The material must obviously be new, in perfect condition and returned in its original packaging.

Together with the material, which must be returned at your own expense (any collect shipment will be refused), please enclose an explanatory letter and the invoice or a photocopy of the invoice. In case of an error on our part or a product defect, the shipment costs will be refunded based on standard postage fees.

Guarantee

Before returning a product, to avoid any misunderstanding please consult with us. Used items : the items are sold under manufacturer warranty. Wear and tear is obviously excluded from this warranty. Any items returned for repair or warranty claim must be clean and dry.

Precautions regarding the use of material

Improper installation or use of equipment and materials for High Wire Adventure Courses is potentially dangerous (risk of death); for your safety you must ensure that you fully master the installation of materials and equipment before use. ALTUS / KOALA EQUIPMENT disclaims any liability or responsibility for accidents.

Compliance with the instructions for use of PPE

Each PPE (Personal Protective Equipment) comes with an instruction manual as laid down by the European standard. It is the buyer's responsibility to comply.

TERMS OF DELIVERY

Shipping costs

The first stage of the confirmation of the order requires that you create an account as the shipping address is important for shipping fees.

Shipping fees are always calculated on a case by case basis, upon receipt of your order.

A quote is then sent indicating the shipping costs for your package and the amount for the materials ordered.

We undertake to send you this quote within 48 hours (French working days).

Upon receipt of our e-mail quote, 3 methods of payment are available to complete your order :

- by credit card through a secured link

- by phone with your credit card number

- by check if your bank is in France.

We can dispatch items to virtually any address in the world. However, warranty issues, manufacturer restrictions and customs laws prevent us from shipping certain products to certain geographical locations.

Delivery

Orders are dispatched the day we receive your payment (depending on the availability of the product and the delivery company).

In France : Delivery time is 48 to 72 hours (depending on the availability of the product and the delivery company).

Availability


In case the product is not in stock, delivery times will be in function of manufacturers' and/or suppliers' deadlines. In the event of unavailability of a product after placing your order, we will notify you by e-mail or phone once we have received the information from the suppliers. Your order will be cancelled and you will be refunded within 30 days of your payment.

> ALTUS / KOALA EQUIPMENT - 1191 route de Bidaille 74930 SCIENTRIER -FRANCE) RCS Thonon les Bains : 411 354 962 00044 / Legal Notice/ Sales terms TEL : 00 33(0)4 50 97 50 19 / e-mail : info@koala-equipment.com

PRICES EUR


REFERENCE	NAME	PRICE
CA04-B100	7x19 WS Galvanized wire rope Ø12 mm (0,47 in) - 100 m reel (328,08 ft)	
CA04-B250	7x19 WS Galvanized wire rope Ø12 mm (0,47 in) - 250 m reel (820,21 ft)	
CA05-B250	6x7 FC Lang's lay galvanized wire rope Ø 12mm (0,47 in) - 250 m reel (820,21 ft)	
CA05-B500	6x7 FC Lang's lay galvanized wire rope Ø12 mm (0,47 in) - 500 m reel (1640,42 ft)	
CA12-B500	6x26 WS Galvanized swaged wire rope IWRC Ø12 mm (0,47 in) - 500 m reel (1640,42 ft)	
CA01-B200	7x19 WS Red plastic coated wire rope EXT Ø12 mm (0,47 in) INT Ø10 mm (0,39 in) - 200 m reel (656,16 ft)	
CA11-B250	19x 7 WSC Rotation resistant Galvanized wire rope Ø12 mm (0,47 in) - 250 m reel	
CA07-10	Ø12 mm (0,47 in) Swaged thimbled wire rope with 2 solid thimbles	
CA08-10	Ø12 mm (0,47 in) Swaged thimbled wire rope with 1 solid thimble	
CA06-10	Ø12 mm (0,47 in) Swaged thimbled 12 mm wire rope with 2 thimbles	
QU130-12	Wire rope clip CE for Ø12 mm (0,47 in) wire rope	
QU052-13	Wire rope clip DIN 741 for Ø12 mm (0,47 in) wire rope	0,69€
QU13	Solid rope thimble S412-1/2	32,57€
QU01-13	Ø13 mm (0,51 in) wire rope thimble	
QU36-13	N°13 Aluminium ferrule for swaging 2 wire ropes Ø12 mm (0,47 in)	
QU55-305	2 Clevis turnbuckle, stroke 305 mm (12 in)	
QU55-457	2 Clevis turnbuckle, stroke 457 mm (17,99 in)	99,00€

REFERENCE	NAME	PRICE
CA04-B100	7x19 WS Galvanized wire rope Ø12 mm (0,47 in) - 100 m reel (328,08 ft)	
CA04-B250	7x19 WS Galvanized wire rope Ø12 mm (0,47 in) - 250 m reel (820,21 ft)	
CA05-B250	6x7 FC Lang's lay galvanized wire rope Ø 12mm (0,47 in) - 250 m reel (820,21 ft)	
CA05-B500	6x7 FC Lang's lay galvanized wire rope Ø12 mm (0,47 in) - 500 m reel (1640,42 ft)	
CA12-B500	6x26 WS Galvanized swaged wire rope IWRC Ø12 mm (0,47 in) - 500 m reel (1640,42 ft)	
CA01-B200	7x19 WS Red plastic coated wire rope EXT Ø12 mm (0,47 in) INT Ø10 mm (0,39 in) - 200 m reel (656,16 ft)	
CA11-B250	19x 7 WSC Rotation resistant Galvanized wire rope Ø12 mm (0,47 in) - 250 m reel	
CA07-10	Ø12 mm (0,47 in) Swaged thimbled wire rope with 2 solid thimbles	\$180,31
CA08-10	Ø12 mm (0,47 in) Swaged thimbled wire rope with 1 solid thimble	\$120,91
CA06-10	Ø12 mm (0,47 in) Swaged thimbled 12 mm wire rope with 2 thimbles	
QU130-12	Wire rope clip CE for Ø12 mm (0,47 in) wire rope	\$1,45
QU052-13	Wire rope clip DIN 741 for Ø12 mm (0,47 in) wire rope	\$0,92
QU13	Solid rope thimble S412-1/2	\$43,35
QU01-13	Ø13 mm (0,51 in) wire rope thimble	\$0,98
QU36-13	N°13 Aluminium ferrule for swaging 2 wire ropes Ø12 mm (0,47 in)	
QU55-305	2 Clevis turnbuckle, stroke 305 mm (12 in)	
QU55-457	2 Clevis turnbuckle, stroke 457 mm (17,99 in)	\$131,77





Skate Slide 174* Pnotta Bridge 175* Needwood Crossing 176* Pännjarve Bridge 177* Zigzag Trapeze 178 Half Zigzag Trapeze 179* Evje Crossing 180* Coed Crossing 181* ø Flying Carpet 182 Half Flying Carpet 183* Criss Crossing 184* Half Criss Crossing 185* Tic Tac Toe 186* Half Tic Tac Toe 187* Itchen Crossing 188 Fuji Crossing 189* Chess Crossing 190* Half Chess Crossing 191 Pirate Crossing 192* Big U





Activities				
	151 Rope Ladder			
R	152 Tree Trunk Ladder			
	153 Scramble Net			
	154 Apple Picker's Ladder			
	155 Log Ladder			
	156 Mallards Ladder			
	157 Parrot Ladder			
×	158* Miller's Stairs			
	159 Climbing Wa ll			
	160* Fisherman's Trap			
	162* Wooden Fisher- man's Trap			

On Rock Activities



* Recommended activities on children's courses





1191 ROUTE DE BIDAILLE 74930 SCIENTRIER FRANCE



@ info@koala-equipment.com









